

HSPOS TECHNOLOGY LIMITED  
5 floor, A1 building, Nanshui industrial park, Sanjiao  
Town, Zhongshan City, Guangdong Province, China  
**Tel** +86 0760-85402097 **Fax** +86 0760-85402097  
Website: [www.hsprinter.com](http://www.hsprinter.com)  
Email: [mikepeng@hsprinter.com](mailto:mikepeng@hsprinter.com)



## HS-58D Series thermal Label Printer Datasheet

### Function

- Product Name: Thermal Label Printer
- Model: HS-58D
- Fashionable design, Splendid quality
- High-speed printing, High performance
- Support Logo download and print
- Support GB 18030
- International language
- Support the ESC/POS Command
- Support USB, Bluetooth interface



### Application



Supermarket



Catering



Store



Tax



Bank



Medical care



Storage



Post

### Parameters

Printing	
Printing method	Direct thermal
Print width	48mm
Column capacity	384 dots/line, 8dots/mm
Printing speed	90mm/s
Interface	USB+Bluetooth

# HSPOS TECHNOLOGY LIMITED

5 floor, A1 building, Nanshui industrial park, Sanjiao Town, Zhongshan City, Guangdong Province, China

Tel +86 0760-85402097 Fax +86 0760-85402097

Website: [www.hsprinter.com](http://www.hsprinter.com)

Email: [mikepeng@hsprinter.com](mailto:mikepeng@hsprinter.com)



Printing paper	57.5±0.5mm×φ50mm
Line spacing	3.75mm (Adjustable by commands)
Column number	58mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese, traditional Chinese - 16 columns
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese, traditional Chinese: 3.0×3.0mm (24×24 dots)
Barcode Character	
Extension character sheet	PC347/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1 251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001(Latvian)/(PC1001)/(PT 151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
Power	
Power adaptor	Input: AC 110V/220V, 50~60Hz
Power source	Output: DC 12V/2A
Cash drawer output	DC 12V/1A
Physical characteristics	
Weight	590g
Dimensions	200×180×130mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0~45°C) humidity(10~80%)
Storage environment	Temperature(-10~50°C) humidity(10~90%)
Reliability	
Printer head life	50KM