

HSPOS TECHNOLOGY LIMITED

No.49,JinShan East Street, ShanJiao Town, Zhongshan
City, Guang Dong Province, China

Tel +86 0760-85402097 **Fax** +86 0760-85402097

Website:www.hsprinter.com

Email:mikepeng@hsprinter.com



HS-KL562 Embedded label module Datasheet

Function

- Low noise, high-speed printing
- Convenient and fast way to get on paper
- Easy to maintain, Print with label paper
- Support label automatic stripping
- Support for 1D, 2D Printing
- Support GB 18030 & Multi-lingual
- with usb+RS232 port



Application



Supermarket



Catering



Store



Tax



Bank



Medical care



Storage



Post

HSPOS TECHNOLOGY LIMITED
No.49,JinShan East Street, ShanJiao Town, Zhongshan
City, Guang Dong Province, China
Tel +86 0760-85402097 **Fax** +86 0760-85402097
Website:www.hsprinter.com
Email:mikepeng@hsprinter.com



Parameters

Printing	Printing Method	Thermal Line
	Printing Speed	100mm/s
	Resolution	8 dots/mm, 384 dots/line
	Effective Printing Width	56mm
Character	Character Set	ASCII, GB18030(Chinese), BIG5 (24*24)
	Print Font	Codepage, ASCII 12×24, 24×24
Paper Spec	Paper Type	Thermal label paper
	Paper Thickness	0.06~0.08mm
	Paper Width	60mm
Barcode		1D: UPC-A, UPC-EEAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128 2D: QR CODE, PDF417, DATAMATRIX
Emulation		ESC/POS
Driver		Win10/2000/NT/XP/Vista/Win7/Win8/Linux/Andriod
Interface		RS-232/USB
Paper Supply Method		Manual loading
Power Supply		DC24V±10%, 3A
size		250*120*90mm
Weight		1.5kg
Environment	Operating Temp	0~ 50 °C
	Operating Humidity	10%~80%