

HSPOS TECHNOLOGY LIMITED
5 floor, A1 building, Nanshui industrial
park, Sanjiao Town, Zhongshan City, Guangdong Province, China
Tel+86 0760-85546950 **Fax**+86 0760-85546950
Website: www.hsprinter.com
Email: info@hsprinter.com



HS-K38 110mm Thermal Label Printer

Function

- Max 108MM Printing width and adjustable mini size 25mm and Max size 108mm
- Support continuous paper, label paper, folded paper, tag paper
- Support windows, MAC, IOS, Android system.
- High-quality printing and low cost
- Low noise and high-speed printing
- Support multiple instruction sets TSPL, ZPL
- With IOS and android Free Apps, you can print anywhere.
- Low power consumption and low operating costs (No Ribbons or Ink cartridges)
- Fashionable design, Splendid quality
- High-speed printing, High performance
- Usb and Bluetooth interface can be choose.



Application



Supermarket



Catering



Store



Tax



Bank



Medical care



Storage



Post



Parameters

| Performance Parameters | Printing mode | Thermal | |
|------------------------|----------------------|--|--|
| | Barcode | 1D | UPC-A/UPC-E/EAN13(JAN13)/EAN8(JAN8)/CODABAR/ITF/CODE39/CODE93/CODE128 |
| | | 2D | QR Code, PDF417 |
| | Effective resolution | 203DPI(8 dots/mm) | |
| | Print width | 108mm | |
| | Print length | 25mm-300mm | |
| | Print speed | 180mm/s | |
| | Print font | Chinese:GB18030 24*24 dots, English:ASCII 12*24 dots | |
| | CPU | 32 bit RISC CPU | |
| | Instruction set | TSPL, | |
| | Storage | RAM | 2M |
| | | Flash | 4M |
| | Testing | sensor | Paper shortage test, paper outlet test, seam test and cover opening test |
| | Medium | Paper type | Continuous paper, label paper |
| | | Roll width | 42.5mm-110mm |
| | | Paper thickness | 0.058-0.22mm |
| | Compatibility | Support OS | XP, Win03, Win7, Win8, Win10, Linux, Mac, Andorid, IOS |
| Physical Parameters | Sound prompt | Buzzer, voice | |
| | Key | Power on key, cover opening key, feed | |
| | Indicator light | Power indicator, error indicator | |
| | Working environment | 0~50℃, 20%~85%(Non-Condensed) | |
| | Storage environment | -20~70℃, 5%~95%(Non-Condensed) | |
| | Interface | USB, BT | |
| | Power output | DC24V/2.5A | |
| | Host Size(L*W*H) | 159*85.5*84mm | |
| | Packing Size(L*W*H) | 208*127*139mm | |
| | Packing Weight | About 623g /1123g | |