

HSPOS TECHNOLOGY LIMITED

5 floor, A1 building, Nanshui industrial park, Sanjiao
Town, Zhongshan City, Guangdong Province, China

Tel +86 0760-85402097 **Fax** +86 0760-85402097

Website: www.hsprinter.com

Email: mikepeng@hsprinter.com



HS-589C Thermal Receipt Printer Datasheet

Function

- Smart appearance
- Easy paper loading
- Low noise thermal printing
- Different interfaces optional
- Front panel make paper replacement easily
- Easily embedded to any kinds of instruments and meters
- Support Cash Drawer port.
- Support usb+Parallel
- Support big Paper Roll Diameter 60mm
- 120mm/s Printing speed



Application



Supermarket



Catering



Store



Tax



Bank



Medical care



Storage



Post



Parameters

Print	Printing Method	Thermal Dot Line
	Printing Speed	120mm/s
	Resolution	8 dots/mm, 384 dots/line
	Effective Printing Width	48mm
Character	Character Set	ASCII, GB2312-80(Chinese)
	Print Font	ANK: 8x16, 9x17, 9x24, 12x24, GBK: 16x16, 24x24
Paper Spec	Paper Type	Thermal paper
	Paper Width	57.5± 0.5mm
	Paper Thickness	60-85μm
	Paper Roll Diameter	Max: 60mm
Reliability	MCBF	5 million lines
Interface		USB+Parallel
Power Supply (Adapter)		12V
Physical	Outline Dimension (WxDxH)	114.8x131.8x82mm
	Installation Port Size	111.09x128.09mm
	Color	black/white
Environment	Operating Temp	5°C ~ 50°C
	Operating Humidity	10% ~ 80%
	Storage Temp	-20°C ~ 60°C
	Storage Humidity	10% ~ 90%