

HSPOS TECHNOLOGY LIMITED  
5 floor, A1 building, Nanshui industrial  
park, Sanjiao Town, Zhongshan City, Guangdong Province, China  
**Tel**+86 0760-85546950 **Fax**+86 0760-85546950  
Website: [www.hsprinter.com](http://www.hsprinter.com)  
Email: [mikepeng@hsprinter.com](mailto:mikepeng@hsprinter.com)



## HS-P80CAI Series Thermal printer with cutter

### Function

---

- 3 inch mobile receipt thermal
- Portable device suited for outdoor usage
- Waterproof design
- Low battery indicator (7.4V, 2000mAh)
- Equipped with lithium battery for 4-8 hours continuous work
- Various interfaces communication and interface capacities
- Bluetooth with high communication speed
- Easy paper loading
- Printer with auto cutter
- High printing speed, up to 80mm/s



### Application

---



Supermarket



Catering



Store



Tax



Bank



Medical care



Storage



Post

HSPOS TECHNOLOGY LIMITED  
 5 floor, A1 building, Nanshui industrial  
 park, Sanjiao Town, Zhongshan City, Guangdong Province, China  
**Tel** +86 0760-85402097 **Fax** +86 0760-85402097  
 Website: [www.hsprinter.com](http://www.hsprinter.com)  
 Email: [mikepeng@hsprinter.com](mailto:mikepeng@hsprinter.com)



## Parameters

| Printing Method          | Thermal Line  |
|--------------------------|---|
| Resolution               | 8 dots/mm, 384 dots/line  |
| Effective Printing Width | 72mm  |
| Printing Speed           | 50-80mm/s   |
| Character Set            | ASCII, GB18030(Chinese), BIG5   |
| Print Font               | ANK: 12 x24, 9 x24 Chinese: 24 x 24   |
| Self-defined Character   | Yes   |
| Barcodes                 | EAN-13, EAN-8, UPC-A, UPC-E, CODE39, CODE93, CODE128, CODABAR, INTERLEAVED 25 |
| Driver                   | Windows XP/Windows Vista/Windows 7/IOS/Linux                                  |
| Graphic                  | Support bitmap downloading  |
| Paper End Sensor         | Yes   |
| Overheating Protection   | Yes   |
| Auto Sleeping            | Yes   |
| Interface                | USB + Bluetooth   |
| Battery                  | DC7.4V, 1.5A rechargeable Li-ion battery                                      |
| Charger                  | DC9V/2A   |
| Printer head life        | 50km  |
| Paper Type               | Thermal paper   |
| Paper Width              | 57.5± 0.5mm   |
| Paper Thickness          | 0.06 to 0.08mm  |
| Paper Roll Diameter      | 40mm (Max.)   |
| Paper Supply Method      | Drop-in Easy loading  |
| Paper Cutting Method     | Manual  |
| Operating Temp/Humidity  | 0-50°C/10%-80%  |
| Storage Temp/Humidity    | -20-60°C / 10%-90%  |
| Dimension (L x W x H)    | 105 x 75 x 37mm   |
| Weight                   | 235g  |